



## **Vu Safe™ Storm Panels WARRANTY**

### **Installation, Service & Removal**

VuSafe™ Storm Panels are a weather protection device, which must be installed in accordance with approved engineering in order to maintain the product warranty. In an event requiring the removal and/or service of any permanently installed hardware (top and bottom mounting channels), it is highly recommended that you contact your dealer for assistance in order to avoid nullifying the product warranty.

### **Breakage**

VuSafe™ Storm Panels - extruded polycarbonate sheets - are warranted against breakage for a period of five (5) years from the date of sale only if breakage is due to manufacturing defect. The warranty is subject to the terms herein. Upon application for any warranty, the original purchaser or authorized installer will receive free panel replacement provided the failed panel and a copy of original purchase are returned to VuSafe Industries, LLC (VSI) or its authorized agent. Alternatively, the company may elect to refund the original cost of the panel.

### **Yellowing**

Polycarbonate panels may become cloudy and yellow as a result of prolonged exposure to sunlight. If excessive yellowing or loss of light transmission occurs during a five (5) year period from the date of sale due to manufacturing defect. VSI will provide replacement panels to the purchaser or certified installer.

### **Conditions**

This warranty applies only to VuSafe™ Storm Panels fabricated, installed, and cleaned according to VSI's recommendations! It is important to note that VuSafe™ Storm Panels are designed for weathering resistance and do NOT provide abrasion resistance; no warranties are extended on the abrasion resistance characteristics of this product. The warranty does not cover installation or fabrication expenses or any other direct or indirect loss, which may result from the panel failure.

**YELLOWING AND LIGHT TRANSMISSION:** The warranty against yellowing and light transmission applies only to clear VuSafe™ Storm Panels. The Yellowness Index (YI) of VuSafe™ Storm Panels, cleaned according to the recommendations of VSI, shall be less than 5 during a five-year period from the date of sale, as determined according to ASTM D1925, as measured with a Gardner Colorimeter (Instrument Conditions: Illuminant C, 2° Observer).

This warranty is limited to excessive yellowing and loss of light transmission due to the degradation of VuSafe™ Storm Panels and does not cover yellowing or light transmission losses due to dirt, atmospheric deposits, or abrasion. Be aware that all outdoor materials are subject to irreversible depositions of atmospheric elements and can be expected to show signs of hazing eventually. Regular, proper cleaning will significantly reduce, but not eliminate, that process. This warranty does not cover abrasion or scratching.

**SURFACE FINISHES:** Powder Coated Aluminum Channels

**NOTE:** VuSafe™ Storm Panels are designed for seasonal use not year-round protection. Year-round exposure to sunlight will hasten the UV degradation of the product.